



LUNEBERG REFLECTORS
MONOSTATIC EQUATORIAL
CIRCULAR POLARIZATION

Zéphyr

Plan #	4LUN04R0008	
R.C.S. Measurements	<p>We guarantee the specifications of the reflector according to plan # 4LUN04R0008. The reflector is delivered with 3 points of measurement (0° / -15° / +15° of sight at 0° of azimuth). The delivered measurement corresponds to the measurement of the lens alone.</p> <p>Further measurement options (patterns, other frequencies...) on specific request.</p>	
Response	<p>Monostatic</p>	
Polarization	<p>Circular. The radars use the circular polarization in particular in order to reduce the droplets effect. The circular radar reflector stands out of the clutter caused by the reflections of the rain because it reflects the signal without inversion of the direction of polarization, contrary to trihedral reflector or flat disk.</p>	
Metallization		<p>Metallization on ± 20° Measurements at ± 15°</p>
Radom	<p>Waterproof composite protection (also against salted ambiance). Acceleration – vibration tests have been passed allowing mounting in supersonic targets</p>	
Standard composite fixing (in option)	<p>Development of any other fixing at request</p> <p>Min RCS values are guaranteed for lenses without fixing</p>	
Specific unit packaging		
⚠ Precautions of use	<p>The response of the lens depends on the environment.</p> <ul style="list-style-type: none"> ● Avoid thick fairing ● Avoid fairing made of dielectrical material with important losses ● Avoid any object (especially metallic) positioned between the lens and the radar (strap, screw...) ● Take care in mounting 	



LUNEBERG REFLECTORS
MONOSTATIC EQUATORIAL
CIRCULAR POLARIZATION

Reference	Frequency range	Measuring frequency (GHz)	Minimum Radar Cross Section guaranteed (sqm)		Diameter of the reflector without fixing		Weight without fixing (kg)
			R.C.S. in the equatorial plane	R.C.S. at $\pm 15^\circ$ of sight	(inches)	(cm)	
XEC09	X	9,375	2,0	à $\pm 15^\circ$ 1,0	9,2	23	2,9

* RCS values are guaranteed for lenses without fixing

